

MPC-165/MPC-365 NARROW FORMAT MICROMANIPULATOR SYSTEM

Our new MP-865 "narrow format" mechanical is designed especially for patch-slice manipulator systems that require more than 2 or 3 pipettes as well as for other setups where space is limited. The MP-865 was designed to minimize the width, allowing as many manipulators to be grouped together as possible. Travel in the Y-axis is shortened (12.5 mm) both to economize on width and because radially oriented manipulators do not require long travel in the traverse axis. Additional travel has been added in the X-axis giving the manipulator 50mm of travel in X, to facilitate fast and easy pipette exchange.

The MP-865 manipulator is designed specifically for systems requiring 4 or more manipulators. To this end, we have put together systems with special pricing for 4, 5 and 6 manipulators, and 2 or 3 dual manipulator controllers. The optional narrow-format stand and linear slide or rotating base is available for mounting the MP-865 mechanical. With the 150 mm throw of the linear slide, the manipulator can be quickly and smoothly retracted out to a

location where there is easy access to the pipette for replacement. A rotating base can be used for mounting to large platform stages like the Sutter MT-78, or smaller Sutter MD Series platforms.

MPC-365 systems are formed by using the popular Sutter MPC-200 dual manipulator controller and ROE-200, with one or more MP-865 mechanicals. A single MPC-200 controllers and ROE-200 can run one or two MP-865 manipulators. A single ROE-200, when paired with two MPC-200 controllers can control up to four MP-865 manipulators. If you require more manipulators in a single setup, you simply duplicate the smaller systems. A new firmware version of the MPC-200/ROE-200 automatically recognizes the MP-865 mechanical and adjusts accordingly.

As a more economical alternative, the MP-865 also pairs with our MPC-100 controller. The MPC-100 integrates the entire controller into the ROE input device in a quiet compact design. Each MPC-100 can control up to two MP-865 manipulators.

ADDITIONAL FEATURES:

- Toggle switch selects which manipulator is connected to input device
- · LED and display indicate active manipulator
- Low-drift mechanical stability
- Narrow MT-73 stand with 150 mm linear slide, and built-in rotating base mounting options



(CONTINUED ON BACK)

SUTTER INSTRUMENT



System includes one TRIO™ MPC-100 MPC-165

controller, one MP-865/M manipulator mechanical, mounting adapter plate, rod holder, 4" dovetail extension, cables, power cord and manual.*

MPC-165-2 MPC-165 with two MP-865/M

mechanicals.*

One MP-865/M manipulator mechanical, MPC-365

one MPC-200 controller and one ROE-200, mounting adapter plate, rod holder, 4 inch dovetail extension, cables,

power cord and manual.*

Same as the MPC-365, but with two MPC-365-2

MP-865/M mechanicals*

MTC-365-3 Same as the MPC-365, but with four

MP-865/M MP-265/M mechanicals, and

two MPC-200 controllers.* Same as the MPC-365, but with four MP-865/M MP-265/M mechanicals, and MTC-365-4

two MPC-200 controllers.* MTC-365-5

Same as the MPC-365, but with five

MP-865/M mechanicals, three MPC-200 controllers, and two ROE-200 user interfaces.*

MTC-365-6 Same as the MPC-365, but with six

MP-865/M mechanicals, three MPC-200 controllers, and two ROE-200 user

interfaces.*

MP-865/M*

The MP-865 manipulator mechanical alone. Includes mounting adapter plate, rod holder, 4 inch dovetail extension, and cable to connect manipulator to controller

* Indicate right- or left-handed setup when ordering



(Shown: MPC-365 with MT-73 stand and optional dPatch® headstage)